



amma earth product

Technical Information Sheet

June 2009

This technical information sheet is intended to provide guidelines for users. Products are guaranteed to give a satisfactory performance only if used as recommended. Liability shall be limited to refund of purchase price or the replacement of a defective product. There are no other warranties expressed or implied.

DESCRIPTION

VOLVOX Clay Decor is water-based, free of volatile organic compounds (VOC's) and has an unlimited choice of colours as it can be coloured with most paint tints or pigments.

VOLVOX Clay Decor is virtually odourless during application so you can paint without having to move out!

VOLVOX Clay Decor absorbs variations in humidity and odours from cooking or smoking etc, providing a more comfortable and healthy living and workplace environment.

VOLVOX Clay Decor is so versatile that no primers or undercoats are needed*. It can be painted onto almost any firm surface, whether interior or, in dry frost-free areas, exterior.

VOLVOX Clay Decor is perfect in creating a warm and cosy feeling in your home. Due to its highly absorbing capabilities, it is also an ideal choice for children's rooms, chemically-sensitive people, asthma sufferers and people with skin problems.

SURFACE PREPARATION

Remove dirt, grease, oil and loose, peeling and flaking material. Fill cracks and holes with a filler. Sand the surface smooth and remove all dust. Light sanding is recommended when painting over firm glossy or semi-gloss paint.

***NOTE** For Darker/Intense Clay Colours on cement joints for New gyprock a priming layer of Mont Blanc(white) is required.

Need help?

Contact 02 47 82 90 09 or email : amma@y7mail.com

APPLICATION

Apply one to two coats of VOLVOX Clay Decor by roller, brush, plastic trowel or spry and spread evenly in all directions. On very absorbent surfaces such as clay, Gyprock, plaster, sandstone etc. application will be easier by dampening the surface with water and/or reducing the first coat with up to 5% water. Allow each coat to dry completely before repainting. Do not reduce final coats. Do not apply in temperatures below 5°C or above 30°C.

Need help?

Contact 02 47 82 90 09 or email : amma@y7mail.com

DRYING AND RECOATING

VOLVOX Clay Decor will normally dry within 2 hours and can then be recoated. In cold or humid conditions drying time may be lengthened.

COVERAGE

Depending on colour, 1 litre will cover approximately 8 sq. metres with covering capacity of 99.50% (test made with Mont Blanc, White).

CLEAN UP

With water, away from drains.

COLOURS

VOLVOX Clay Decor is available in 7 base colours of Mont Blanc, Ivory, Dacar, Sienna, Terracotta, Smoke and Polar, that are also used for creating 126 designer colours. 25 colours have been selected in our special collection by European colour coordinators. Please ask for colour charts. Further colour matching is available from selected paint places and Amma Earth Products, Katoomba NSW.

STORAGE AND SHELF LIFE

Store tightly sealed, cool but frost free. Minimum shelf life for unopened and properly stored containers is 12 months.

SAFETY

Even though non-toxic, Please keep away from children.

DISPOSAL

Allow unwanted paint to dry. Solid matter can be disposed of via the normal garbage collection service.

INGREDIENTS: Water, clay, chalk, China clay, vinegar ester, cellulose, 0.1% paint conservator, titanium dioxide (Only in white Volvox Clay Decor).

DISCLAIMER

It is recommended that the user tests the product on the intended surface to ensure its suitability.

Made in Germany

For further information contact
Amma Earth Products
17/26 Megalong St.
Katoomba NSW 2780
02 47 82 90 09
0416 101 613
amma@y7mail.com